



5 cable system Taps and splitter


- 2 way splitter and one way taps of 4 SAT+1 terrestrial signals
- low losses
- switchable DC pass to tap H outputs
- accepts central pin \varnothing 1.2 mm max.

SS504 2 way splitter	SS515 1 way 15 dB tap
SS510 1 way 10 dB tap	SS520 1 way 20 dB tap



Technical specifications

T Y P E		SS504	SS510	SS515	SS520
Ordering number		01747	01748	01749	01750
Frequency range	SAT IF	950-2400 MHz			
	Terr. TV	5-862 MHz			
Through loss	SAT IF	4 dB	1.5 dB	1.1 dB	0.7 dB
	Terr. TV	4 dB	1.5 dB	1.2 dB	1 dB
Tap loss	SAT IF	4 dB	8 ÷ 12 dB	13 ÷ 17 dB	18 ÷ 22 dB
	Terr. TV	4 dB	10 dB	15 dB	20 dB
SAT inputs decoupling	SAT IF	30 dB			
	Terr. TV	30 dB			
DC pass through		2 A max.			
Operating temperature range		-20° ÷ + 50° C			
Dimensions/Weight (packed)		120x120x34 mm/0.3 kg			



4 way splitter

- 4 way splitter of 4 SAT+1 terrestrial TV signals
- switchable DC pass to tap H outputs
- accepts central pin \varnothing 1.2 mm max.



Technical specifications

T Y P E		SSQ508
Ordering number		01751
Frequency range	SAT IF	950-2400 MHz
	Terr. TV	5-862 MHz
Through loss	SAT IF	8 dB
	Terr. TV	8 dB
SAT inputs decoupling	SAT IF	30 dB
	Terr. TV	30 dB
DC pass through		2 A max.
Operating temperature range		-20° ÷ + 50° C
Dimensions/Weight (packed)		254x120x34 mm/0.4 kg

